HellermannTyton

181-05501 Article Number:

Description:

Solid Cable and Wiring Duct, .5" x .5", Non-Adhesive, PVC, Gray, 120 ft/carton

HellermannTyton

Base Data		
	Local Order Number	181-05501
	Туре	SD.5X.5
	Color	Gray (GY)
	Features and Benefits	 A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement. Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)
	Quantity Per	carton
	Product Description	HellermannTyton's Pro-Duct wiring duct efficiently routes and protects wire and cable. Manufactured from high impact, rigid PVC, Pro-Duct includes solid, slotted and high density slotted styles. Pro-Duct comes in standard colors of white, gray and black in 6 foot lengths.
	Technical Description	Non-Adhesive
	Short Description	Solid Cable and Wiring Duct, .5" x .5", Non-Adhesive, PVC, Gray, 120 ft/carton
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	0.5"
	Width W (Metric)	12.7mm
	Width W2 (Imperial)	0.76"
	Width W2 (Metric)	19.3mm
	Height H (Imperial)	0.55"
	Height H (Metric)	14mm
	Mounting Hole Centers (Imperial)	4.0"

181-05501

HellermannTyton

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
ROHS Compliant	Yes
Certification/Specification	CSA
UL Recognized (US)	Yes
Package Quantity (Imperial)	120ft
Package Quantity (Metric)	36.6m
Customs Number(Schedule B)	3925900000
	Material Shortcut Flammability Operating Temperature ROHS Compliant Certification/Specification UL Recognized (US) Package Quantity (Imperial) Package Quantity (Metric)