

Article Number: 170-03200



Description: Braided Wrap, Aluminum Laminated Fiberglass, 4' Long

Stick, .75" Dia, AL/GF, Silver, 50/box

| Base Data | | |
|-----------------------------|------------------------------|--|
| | Local Order Number | 170-03200 |
| | Туре | BSHTTSW34LB |
| | Color | Silver (SR) |
| | Features and Benefits | A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion. Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments. Cuts with ordinary scissors for fast, easy application. |
| | Quantity Per | box |
| | Product Description | Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance. |
| | Short Description | Braided Wrap, Aluminum Laminated Fiberglass, 4' Long Stick, .75" Dia, AL/GF, Silver, 50/box |
| Product Dimensions | | |
| | Length L (Imperial) | 4.0ft |
| | Length L (Metric) | 1.22m |
| | Reel Length (imperial) | 4.0ft |
| | Diameter D (imperial) | 0.75" |
| | Diameter D (metric) | 19.05mm |
| | Nominal Diameter (Imperial) | 3/4" |
| | Nominal Diameter (Metric) | 19.05mm |
| | Wall Thickness WT (Imperial) | .042" |
| | Wall Thickness WT (Metric) | 1.06mm |
| Material and Specifications | | |
| | Material | Glass fiber with aluminium foil (GF-AL) |
| | Material Shortcut | GF-AL |

generated on: 4/28/2017

170-03200



| Material and Specifications | Flammability | non flammable |
|--------------------------------|-----------------------------|-----------------------------------|
| | Operating Temperature | -76°F to +491°F (-60°C to +255°C) |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 50 |
| | Package Quantity (Metric) | 50 |
| | Customs Number(Schedule B) | 7019901000 |

generated on: 4/28/2017