

RJ45 Adapter and CAT5 System Cables

wiHUBB® AND ZONE5™ LIGHTING CONTROLS



RJ45ADAPTER

PROJECT INFORMATION

Project Name _____

Catalog No. _____

Date _____

Hubbell Control Solutions' RJ45 Adapter and CAT5 system cables are designed to be used with HCS low voltage occupancy and daylight sensors. The adapter replaces the Quick-To-Install (QTI) connectors previously used by the *wiHUBB* and *Zone5* occupancy and daylight sensors and enables devices to connect to control modules (e.g. *wiHUBB* Smart Pack, *Zone5* Control Module, etc) using standard CAT5 cable.

PRODUCT FEATURES

- Supports *wiHUBB* and *Zone5* occupancy and daylight sensors
- Plenum rated
- Five-year limited warranty
- Low voltage device: 24 Vdc

General Specifications

Electrical	4 Terminal Connections - Red: +24V - Blue: Occupancy Sensor Input - Yellow: Photocell/Daylight Sensor Input - Black: Common Class 2 device Max Cable Length Supported: 300-ft from device to control module
Plenum Rated	Complies with requirements for use in a plenum area
Construction	Material: SABIC NORYL HS2000X
Dimensions	Size: 2.168"L x 1.093"W x 0.995"H
Weight	0.8 oz
Color	Gray
Mounting	Adapter may be mounted using a zip-tie (not included) or with a #8 or #10 mounting screw (not included)
Warranty	Five-year limited

Ordering Information

RJ45 Adapter

--	--

MODEL/DESCRIPTION	
RJ45ADAPTER	RJ45 Adapter for <i>wiHUBB</i> ® & <i>Zone5</i> ™ Occupancy and Daylight Sensors
RJ45ADAPTER-10	RJ45 Adapter for <i>wiHUBB</i> & <i>Zone5</i> Occupancy and Daylight Sensors - 10 Pack
RJ45ADAPTER-50	RJ45 Adapter for <i>wiHUBB</i> & <i>Zone5</i> Occupancy and Daylight Sensors - 50 Pack

CAT5 System Cables

--	--

MODEL/DESCRIPTION	
CAT5-3IN-BL	CAT5 Jumper Cable for <i>wiHUBB</i> & <i>Zone5</i> Lighting Control Switches, Plenum Rated, 3in, Blue
CAT5-10F-BL	CAT5 Cable for <i>wiHUBB</i> & <i>Zone5</i> Lighting Control Switches, Plenum Rated, 10ft, Blue
CAT5-50F-BL	CAT5 Cable for <i>wiHUBB</i> & <i>Zone5</i> Lighting Control Switches, Plenum Rated, 50ft, Blue
CAT5-100F-BL	CAT5 Cable for <i>wiHUBB</i> & <i>Zone5</i> Lighting Control Switches, Plenum Rated, 100ft, Blue
CAT5-10F-WH	CAT5 Cable for <i>wiHUBB</i> & <i>Zone5</i> Occupancy & <i>WASP</i> ™2 Sensors, Plenum Rated, 10ft, White
CAT5-50F-WH	CAT5 Cable for <i>wiHUBB</i> & <i>Zone5</i> Occupancy & <i>WASP</i> 2 Sensors, Plenum Rated, 50ft, White
CAT5-100F-WH	CAT5 Cable for <i>wiHUBB</i> & <i>Zone5</i> Occupancy & <i>WASP</i> Sensors, Plenum Rated, 100ft, White
CAT5-10F-GN	CAT5 Cable for <i>wiHUBB</i> & <i>Zone5</i> Daylight Sensors, Plenum Rated, 10ft, Green
CAT5-50F-GN	CAT5 Cable for <i>wiHUBB</i> & <i>Zone5</i> Daylight Sensors, Plenum Rated, 50ft, Green
CAT5-100F-GN	CAT5 Cable for <i>wiHUBB</i> & <i>Zone5</i> Daylight Sensors, Plenum Rated, 100ft, Green
CAT5-3IN-YL	CAT5 Jumper Cable for <i>Zone5</i> Master/Row Control Switches, Plenum Rated, 3in, Yellow
CAT5-50F-YL	CAT5 Cable for <i>Zone5</i> Master/Row Control Switches, 50ft, Yellow
CAT5-100F-YL	CAT5 Cable for <i>Zone5</i> Master/Row Control Switches, 100ft, Yellow

wiHUBB & *Zone5* Cable Cross Reference

PREVIOUS <i>wiHUBB</i> & <i>ZONES</i> CABLE PART NUMBERS	NEW CABLE PART NUMBER
WIH-CAB-3IN-BL Z5-CAB-3IN-BL	CAT5-3IN-BL
WIH-CAB-10F-BL Z5-CAB-10F-BL	CAT5-10F-BL
WIH-CAB-50F-BL Z5-CAB-50F-BL	CAT5-50F-BL
WIH-CAB-100F-BL Z5-CAB-100F-BL	CAT5-100F-BL
WIH-CAB-10F-WSP WIH-CAB-50F-WH WIH-CAB-50F-WSP Z5-CAB-50F-WH Z5-CAB-50F-WSP	CAT5-10F-WH CAT5-50F-WH
WIH-CAB-100F-WH WIH-CAB-100F-WSP Z5-CAB-100F-WH Z5-CAB-100F-WSP	CAT5-100F-WH
Z5-CAB-10F-GN	CAT5-10F-GN
WIH-CAB-50F-GN Z5-CAB-50F-GN	CAT5-50F-GN
WIH-CAB-100F-GN Z5-CAB-100F-GN	CAT5-100F-GN
Z5-CAB-3IN-YL	CAT5-3IN-YL
Z5-CAB-50F-YL	CAT5-50F-YL
Z5-CAB-100F-YL	CAT5-100F-YL

SPECIAL NOTES:

1. When cutting CAT5 cable to specific lengths, the cable pin out is as follows:

PIN NO.	WIRE COLOR
1	WHITE with ORANGE STRIPE
2	ORANGE
3	WHITE with GREEN STRIPE
4	BLUE
5	WHITE with BLUE STRIPE
6	GREEN
7	WHITE with BROWN STRIPE
8	BROWN



HUBBELL
Control Solutions